PATENT ABSTRACTS OF JAPAN

(11) Publication number:

05-029406

(43) Date of publication of application: 05.02.1993

(51)Int.Cl.

H01L 21/66 G01R 1/073

GOIR 31/26

(21)Application number: 03-178179

(71)Applicant: MITSUBISHI ELECTRIC CORP

(22) Date of filing:

18.07.1991

(72)Inventor: NAKAO SHIN

(54) SEMICONDUCTOR INSPECTION APPARATUS

(57) Abstract:

PURPOSE: To obtain a semiconductor inspection apparatus wherein, irrespective of the parallelism of the surface of a semiconductor wafer to the surface of an inspection board, the good electric contact of an electrode pad on the semiconductor wafer with a bump electrode on the inspection board is ensured and the reliability of an inspection is increased.


CONSTITUTION: A plurality of wiring patterns 3a, 3b which have been connected electrically by a through hole 4 are formed on both faces of a probe card 1. A plurality of wiring patterns 5a, 5b which have been connected electrically by a through hole 6 are formed on both faces of an inspection board 2. The inspection board 2 is supported elastically by the probe card 1 in a

state that the wiring pattern 5a has been connected electrically to the wiring pattern 3b by means of a tungsten wire 13. A bump electrode 14 which is provided with a sharp tip shape is formed at the end part of the wiring pattern 5b on the inspection board 2.



[Date of request for examination]

[Date of sending the examiner's decision of



BEST AVAILABLE COPY

OCT. 6. 2005 3:38PM

KIRTON & MCCONKIE

NO. 170 P.P. 8: of 2

rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office